



Fig. 1

### ET型

尺寸Dim 型号 Type	图形 Fig.	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	F (mm)	G (mm)	H (mm)	C <sub>1</sub> (mm <sup>-1</sup> )	Le (mm)	Ae (mm <sup>2</sup> )	Ve (mm <sup>3</sup> )
ET11	1	11±0.25	15±0.3	3.5±0.25	10.18±0.2	7.5±0.25	9±0.25	1.75±0.2	3±0.2	0.724	28.50	39.31	1120.38
ET20	1	20.1+0.6/-0.3	20.1+0.6/-0.3	4.00±0.2	4.40±0.2	15.9MIN	15.9MIN	2.00±0.2	2.00±0.2	2.94	50.50	15.97	806.60
ET20SC	1	20.1+0.6/-0.3	20.1+0.6/-0.3	4.00±0.2	5.40±0.2	15.9MIN	15.9MIN	2.00±0.2	2.00±0.2	2.39	50.5	21.1	1065.55
ET20/25	1	20.1±0.4	26.3±0.5	4.00±0.2	5.4±0.2	16.1±0.4	21.6±0.4	2.0±0.2	2.35±0.2	2.77	61.89	22.36	1389.9
ET23	1	23.15±0.3	21.5±0.3	3.75±0.2	3.85±0.2	19.15MIN	17.4MIN	2.00±0.15	2.05±0.15	3.75	56.30	15.00	844.48
ET24	1	24.2±0.5	24.2±0.5	4.00±0.3	4.00±0.3	19.0MIN	19.0MIN	2.40±0.15	2.40±0.15	3.47	60.80	17.50	1063.56
ET24A	1	24.45±0.4	24.45±0.4	4.00±0.3	4.00±0.3	19.2MIN	—	—	—	3.35	61.00	18.20	1110.20
ET24B	1	24.2±0.4	24.2±0.4	4.00±0.2	4.00±0.2	19.0MIN	19.0MIN	2.40±0.15	2.40±0.15	3.43	61.00	17.80	1085.76
ET25	1	25.5±0.5	25.5±0.5	5.00±0.3	5.00±0.3	—	—	—	—	2.26	62.30	27.60	1719.48
ET26	1	26.1±0.3	26.1±0.3	4.60±0.2	4.60±0.2	20.9MIN	20.9MIN	2.60±0.15	2.60±0.15	2.89	65.80	22.80	1500.24
ET28	1	28.7±0.4	28.7±0.4	5.00±0.2	5.00±0.3	22.2MIN	22.2MIN	2.90±0.15	2.90±0.15	2.67	71.10	26.80	1891.26
ET28B	1	28.2±0.4	28.2±0.4	5.00±0.3	5.00±0.3	—	—	—	—	2.57	71.20	27.70	1972.24
ET35A	1	35.3±0.7	35.3±0.8	7.50±0.3	7.50±0.3	26.5MIN	26.5MIN	4.00±0.2	4.00±0.2	1.48	86.60	58.60	5074.76